

# 5 Port Pilot Operated Solenoid Valve Rubber Seal, Non Plug-in Series **VFR3000**

## How to Order

**Non plug-in** **30 – VFR3** **1** **4** **0** **1** **D** **02** Individual electrical entry

**Conforming to CSA standard**

**Symbol**

1	2 position single 
2	2 position double 
3	3 position closed center 
4	3 position exhaust center 
5	3 position pressure center 

**Body option**

0	Standard
---	----------

**Pilot type**

Nil	Internal pilot
R *	External pilot

\* Option

**Coil rated voltage**

1	100 VAC, 50/60 Hz
2	200 VAC, 50/60 Hz
3 *	110 to 120 VAC, 50/60 Hz
4 *	220 VAC, 50/60 Hz
5	24 VDC
6 *	12 VDC
7 *	240 VAC, 50/60 Hz

\* Option

**Piping (P, A, B, EA, EB port)**

Nil	Side ported
B *	Bottom ported

\* Option

**Port size (P, A, B, EA, EB port)**

Nil	Without sub-plate
02	1/4
03	3/8

\* For bottom ported: 1/4

**Thread type**

Nil	Rc
N	NPT
T	NPTF
F	G

**Pilot valve manual override**

Nil: Non-locking push type 	B*: Locking type B (Tool required) 
A*: Non-locking push type A (Extended) 	C*: Locking type C (Lever) 

\* Option

**Option**

Nil	None
Z	With light/surge voltage suppressor

**Electrical entry**

D: DIN terminal

Refer to the standard product for product specifications, dimensions and model selection procedures.