






5 Port Pilot Operated Solenoid Valve Rubber Seal, Non Plug-in Series **VFR4000**

How to Order

Non plug-in **30** - **VFR4** **4** **0** - **1** **D** - **03** **Individual electrical entry**

Conforming to CSA standard

Symbol

1	2 position single 
2	2 position double 
3	3 position closed center 
4	3 position exhaust center 
5	3 position pressure center 

Body option

0	Standard
1*	Direct manual override

* Option

Pilot type

Nil	Internal pilot
R*	External pilot

* Option

Coil rated voltage

1	100 VAC, 50/60 Hz
2	200 VAC, 50/60 Hz
3*	110 to 120 VAC, 50/60 Hz
4*	220 VAC, 50/60 Hz
5	24 VDC
6*	12 VDC
7*	240 VAC, 50/60 Hz

* Option

Piping (P, A, B, EA, EB port)

Nil	Side ported
B*	Bottom ported

* Option: Bottom ported is not available for external pilot.

Port size (P, A, B port)





Nil	Without sub-plate
03	3/8
04*	1/2

EA, EB port: 3/8

Thread type

Nil	Rc
N	NPT
T	NPTF
F	G

Pilot valve manual override


Nil: Non-locking push type 	B*: Locking type B (Tool required) 
A*: Non-locking push type A (Extended) 	C*: Locking type C (Lever) 


* Option

Option

Nil	None
Z	With light/surge voltage suppressor

Electrical entry

D: DIN terminal


 Refer to the standard product for product specifications, dimensions and model selection procedures.